

FS-3800N Specifications

BASIC SPECIFICATIONS:

Configuration:	Desktop Network Monochrome Printer with Standard 500 Drawer plus 100 Sheet Multi-Purpose Tray
Resolution:	Fast 1200 dpi (1800 x 600), 600 x 600 dpi, 2400 x 600 dpi (w/KIR)
Printer Memory:	Standard 32MB, upgradable to 272MB via 100 pin DIMMs; Standard CF Card Slot (Type 1), Micro Drive Slot (up to 1GB)
Electrical Requirements:	120V, 60Hz, 7.2A
Dimensions:	13.6"W x 18.1"D x 11.8"H
Weight:	28.7 lbs
Max Duty Cycle:	100,000 Pages

CONTROLLER SPECIFICATIONS:

Controller:	PowerPC405 200 MHz
Supported PDL / Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL5e), KPDL2 (PS2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL XL/5e, 80 Outline Fonts for KPDL2
Windows™ OS Compatibility:	Windows™ 95/98/NT4.x/2000/XP
Novell™ OS Compatibility:	Novell Netware™ 3.x/4.x/5.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)
Connectivity / Interface:	Standard Parallel IEEE1284, Serial RS-232C, IB-21e 10/100BaseTX
KUIO LV Enhancement Slots (1):	Optional IB-20 10/100BaseTX, 10Base2; Optional IB-22 Enhanced Wireless NIC
Supported Protocol:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows™, PPD for Mac, PPD for Linux/UNIX
Utilities:	KM-NET Viewer, KM-NET Remote Operation Panel, KM-NET Job Manager, KM-NET Printer Disk Manager, Network Advanced Setup Utilities, PRESCRIBE Utilities

OUTPUT SPEEDS:

Warm-Up Time:	Less than 35 Seconds
First Print Out:	Less than 9.0 Seconds
Pages Per Minute:	25 Letter

PAPER SUPPLY:

Standard Paper Sources:	500 Sheet Drawer, 100 Sheet MPT
Drawer Paper Size:	8.5" x 11", 8.5" x 14", A4, B5, A5
MPT Paper Size:	5.5" x 8.5", 8.5" x 11", 8.5" x 14", A4, B5, A5 Custom (2.8" x 5.8" - 8.5" x 11.7")
Std/Max Paper Capacity:	600 Sheets/2600 Sheets
Paper Weight:	16-28 lb Bond via Paper Drawer, 16 lb Bond - 110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

PAPER HANDLING OPTIONS:

DUPLEX UNIT: DU-60

Paper Size:	8.5" x 11", A4, B5, A5
Paper Weight:	16 - 28 lb Bond
Dimensions / Weight:	13.6"W x 20.5"D x 4.2"H/10.1 lbs

PAPER DRAWER: PF-60

Paper Capacity:	500 Sheets
Max. Drawers:	3
Paper Weight:	16 - 28 lb Bond
Paper Size:	8.5" x 11", 8.5" x 14", A4, B5, A5
Dimensions / Weight:	13.6"W x 17.8"D x 4.1"H/8.4 lbs

PAPER FEEDER: PF-8E

Paper Capacity:	2,000 Sheets
Max. Drawers:	1
Paper Weight:	16 lb Bond - 110 lb Index
Paper Size:	8.5" x 11", A4, B5, A5
Dimensions / Weight:	13.6"W x 14.8"D x 13.9"H/16.6 lbs

BULK STACKER: HS-8E

Stack Capacity:	2,000 Sheets
Paper Weight:	16 lb Bond - 110 lb Index
Paper Size:	8.5" x 11", A4, B5, A5
Dimensions / Weight:	13.6"W x 13.1"D x 14.7"H/15.9 lbs

5-BIN MAILBOX: SO-60

Number of Trays:	5
Mailbox Capacity:	200 Sheets: 8.5" x 11", A4, B5, A5; 100 Sheets: 8.5" x 14"
Paper Weight:	16 - 28 lb Bond
Dimensions / Weight:	13.6"W x 6.7"D x 12.4"H/11.7lbs

ADDITIONAL OPTIONS:

Envelope Feeder (EF-60), Face-Up Tray (FT-200), Face-up Tray for DU-60, Base for PF-8E/HS-8E (PB-60), Legal Tray for PF-60 (PC-60 LGL), Letter Tray for PF-60 (PC-60 LTR), Barcode Reader

CONSUMABLES:

TK-60:	20,000 pages @ 5% Coverage
	* Ships with 10,000 pages @ 5% Coverage



Specifications and design are subject to change without notice. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc.
225 Sand Road, PO Box 40008,
Fairfield, NJ 07004-0008, USA
©2003 Kyocera Mita America, Inc.
www.kyoceramita.com

