

FS-C5015N SPECIFICATIONS

BASIC SPECIFICATIONS:

Configuration:	Color Tandem Network Printer with Standard 500 Sheet Drawer, 100 Sheet Multipurpose Tray, Optional Duplex, Additional Paper Drawers and Hard Disk Drive
Resolution:	600 x 600 DPI (Multi-bit)
Printer Memory:	Standard 128MB, Upgradeable to 640MB via 100 Pin DDR DIMMs, Standard CF Card Slot (Type 1) Optional Hard Disk Drive
Electrical Requirements:	120V, 60Hz, 9.5A
Dimensions:	13.6"W x 18.5"D x 15.2"H
Weight:	52.9 lbs
Max Duty Cycle:	50,000 Pages per Month

CONTROLLER SPECIFICATIONS:

CPU/MHz:	Embedded PowerPC750CXr/400MHz
Supported PDL / Emulations:	PRESCRIBE, KPDL3 (PS3), PCL 6 (PCL 5c, PCL XL)
Fonts:	80 Outline Fonts for KPDL3 and PCL 5c/XL, 1 Bitmap Font
Windows® OS Compatibility:	Windows® 95/98/Me/NT4.x/2000/XP
Novell® OS Compatibility:	Novell NetWare® 3.x/4.x/5.x/6.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100 BaseTX, Hi-Speed USB 2.0
KUIO LV Expansion Slot (1):	Optional IB-23 Secure Network Interface; Optional Printer Hard Disk Drive
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows®, PPD for Mac, PPD for Linux/Unix, Certified Uni Driver, Windows® 64-bit Drivers
Web Interface:	Kyocera Command Center
Utilities:	KM-NET Admin, KM-NET Viewer, KM-NET for Clients, PDF Direct Print, KM-NET for Accounting, PRESCRIBE Utilities

OPTIONAL NETWORK INTERFACE: IB-23

Optional Network Interface supports IPv6, Security and Compliance Security Protocols:	SSL/TLS(HTTPS); SNMPv3
---	------------------------

PAPER SUPPLY:

Standard Paper Sources:	500 Sheet Drawer, 100 Sheet MPT
Drawer Paper Size:	8.5" x 11", 8.5" x 14", A4, A5, B5
MPT Paper Size:	8.5" x 11", 8.5" x 14", A4, A5, B5 Custom: 2.8" x 5.4" - 8.5" x 14"
Std/Max Paper Capacity:	600/1,100 Sheets
Maximum Paper Sources:	Three
Paper Weight:	16 - 28 lb Bond via Paper Drawers, 16 lb Bond - 110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Cardstock, Postcards, Envelopes

OUTPUT SPEEDS:

Warm-Up Time:	Within 80 Seconds
First Print Out Color:	16.0 Seconds
First Print Out Monochrome:	16.0 Seconds
Pages Per Minute (Color/Mono):	17/17 Letter, 16/16 A4, 14/14 Legal

PAPER HANDLING OPTIONS:

DUPLEX UNIT: DU-301

Paper Size:	8.5" x 11", 8.5" x 14", A4, A5, B5
Paper Weight:	16 - 28 lb Bond
Dimensions / Weight:	13.6"W x 22"D x 9.7"H / 12.3 lbs

PAPER DRAWER: PF-60

Paper Capacity:	500 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	8.5" x 11", 8.5" x 14", A4, A5, B5
Dimensions/Weight:	13.6"W x 17.8"D x 4.1"H / 8.4 lbs

FACE-UP TRAY: PT-300

Paper Capacity:	250 Sheets for Printer, 100 Sheets for Duplexer (DU-301)
-----------------	---

OPTIONS:

HARD DISK DRIVE:

Enables Document Printing and e-MPS Functions:
Private Print, Job Storage, Quick Copy Proof and Hold, Virtual MailBoxes

CONSUMABLES:

TK-522K:	Black Toner* 6,000 Pages @ 5% Coverage*
TK-522Y:	Yellow Toner* 4,000 Pages @ 5% Coverage**
TK-522M:	Magenta Toner* 4,000 Pages @ 5% Coverage**
TK-522C:	Cyan Toner* 4,000 Pages @ 5% Coverage**

*ships with 3,000 Pages @ 5% Coverage

**ships with 2,000 Pages @ 5% Coverage

Kyocera's objective is to manufacture superior products with the lowest Total Cost of Ownership (TCO), and have little or no impact on the environment. Kyocera's ECOSYS® Technology provides customers with a printing solution that incorporates life-long consumables and the lowest cost per print.

The operating costs of traditional cartridge-based page printers can easily exceed more than three times the original purchase price during the life of the product. By utilizing Kyocera's proprietary ECOSYS® Technology, a user can typically recoup a printer's purchase price in one year or less.



Document Solutions

Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com.
All trademarks and trade names are the property of their respective owners.
Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008,
Fairfield, NJ 07004-0008, USA
© 2006 Kyocera Mita America, Inc.
Item Code # 855D400058



www.kyoceramita.com